

ECO-SERIES 800

Triac Technology

ECODIM822 - ECODIM823



Modular remote dimmer 750W

Description

- Leading edge dimmer
- Suitable for light bulbs and wire-wound transformers, dimmable halogen 230V, dimmable "leading edge" electronic transformers
- Operation/control electrically insulated from the mains
- Operation with potential-free button (ECODIM822)
- Operation with 12-24Vac/dc pulse (ECODIM823)
- Suitable for up to 750W

Functions

- Memo function
- Room function
- Burglar or alarm function
- Delayed dimming
- Adjustable dimming speed
- General switching on (individually programmable)
- General switching on/off
- Delayed switching off (3min)

Technical specifications

| | |
|--------------|--|
| Principle | Triac controlled /leading edge |
| Connection | Screw connector |
| Output | Up to 750W |
| Temperature | At full load Tc 60°C |
| Dimensions | 2 DIN modules wide, 35mm |
| Weight | 205g |
| Safety | Microprocessor-controlled thermal protection |
| Installation | On DIN rail |
| Load | 650W dimmable "leading edge" electronic transformers 750W light bulb 700W dimmable halogen 230V |
| Operation | Standard potential-free push button (ECODIM822) Pulse 12-24Vac/dc (ECODIM823) Special functions: Memo, dimming speed, ... are to be found under the front panel |

